

Model 420A

Vacuum Package Machine



Model 420A



Safety and Convenience Features

Berkel Model 420A is a reliable, high production floor model vacuum package machine designed to meet most high-volume foodservice portion control and product storage and food retail needs. The unit offers two spacious stainless steel chambers, powerful, high quality pump and four 17" seal bars that provide a high integrity double seal with electric cut-off. The 420A offers an anaerobic gas flush to maintain product color in the vacuum package, extend shelf live and/or to provide a pillow-pack seal to protect the product. Unit is simple to operate and maintain.

Standard Features

- ➤ Floor model with a stainless steel housing and double 27" (686 mm) x 24" (610 mm) x 8" (203 mm) chamber
- ➤ Four 17" (432 mm) seal bars provide high integrity double sealing with electric cut-off
- ➤ Powerful, high quality 63 m³/h Busch pump and vacuum dial gauge
- ➤ 1-speed, 3 HP motor, totally enclosed, permanently lubricated ball bearings, thermally protected
- ➤ Furnished in 220/60/3, 16 amp, AC, ETL listed
- ➤ Vacuum intervals of 1 to 99 seconds
- ➤ Gas flush for the addition of an anaerobic gas mixture and/or pillow-pack seal
- ➤ Simple to operate electronic, touch pad controls with nine storable programs
- ➤ Attached 6-foot, flexible, 3-wire cord for grounded receptacle

Accessories

- ☐ Air Assist
- ☐ Soft Air

Approved By:_	
Date	



Model 420A

Vacuum Package Machine

Model No.	Chamber S Width	ize Depth	Height	Seal Bars	Seal Bar Length	Product Dim Width A	nensions Depth B	Height C
420A	27" (686 mm)	24" (610 mm)	8" (203 mm)	4	17" (432 mm)	52" (1321 mm)	31" (787 mm)	43" (1092 mm)

Pump m³/h	Electrical	Weight	Box Dimensio Width	Height	
63	220/60/3	Net 468 lbs. (213 kg) Ship 625 lbs (284 kg)	60" (1524 mm)	35" (889 mm)	46" (1168 mm)

Specifications

Finish/Construction: Floor model with stainless steel housing and two vacuum chambers.

Pump: Powerful, high quality, 63 m³/h Busch pump and vacuum dial gauge.

Electrical: Furnished in 220/60/3, 16 amp, AC, ETL listed.

Vacuum Chamber: Two, stainless steel 27" (686 mm) x 24" (610 mm) x 8" (203 mm) chamber. Vacuum intervals of 1 to 99 seconds.

Seal Bar(s): Four 17" (432 mm) seal bars provide high integrity double sealing with electric cut-off.

Gas Flush: Provides for the addition of an anaerobic gas mixture and/or pillow-pack seal.

Controls: Simple to operate electronic, touch pad controls with nine storable programs.

Motor: 1-speed, 3 HP, totally enclosed, permanently lubricated ball bearings, thermally protected.

Cord and Plug: Attached 6-foot, flexible, 3-wire cord for grounded receptacle.

Warranty: All parts, service and travel coverage for one year, excluding wear items.

As we continually strive to improve our products, specifications are necessarily subject to change without notice.



